

M-800-L4

WHEELBARROW WHEEL

wheelbarrow wheel Pneumatic tire and with steel rim

M-800-L4 pneumatic wheelbarrow wheel with steel rim.

- Pneumatic 4ply tire.
- 'PLY' rating is used to state how many plies (layers) of rubber were woven into the construction of the tire. This rating indicates the strength and carrying capacity of the tire.
- Steel rim with double closed ball bearings.
- Ø20mm axle, with powder-coated layer.
- Axle length 150mm. is standard length (other sizes are available).
- Very strong and stays on course.
- Capacity: 250 Kg.
- Rim is completely powder-coated in gray. Resistant powder coating. (no solvents, less harmful to the environment).



- Pneumatic 4ply tire
- Steel rim with double closed ball bearings.
- Axle Ø20mm with powder-coated layer.
- Axle length 150mm. is standard length (other sizes are available).
- Rim is completely powder-coated in gray
- Very strong and stays on course.



11170
M-800-L4-15

Cap. (kg)	Dimensions ØxW (mm)	Weight (kg)	Axle length (mm)	Axle Ø (mm)	Tire	Material tire	Material rim	Article	Art. nr
250	400-8/16x4" 400x100	3	150	20	Pneumatic	4ply rubber	Steel, gray powdercoated	M-800-L4-15	11170
250	400-8/16x4" 400x100	3	100	20	Pneumatic	4ply rubber	Steel, gray powdercoated	M-800-L4-10	12420
250	400-8/16x4" 400x100	3	130	20	Pneumatic	4ply rubber	Steel, gray powdercoated	M-800-L4-13	13566
250	400-8/16x4" 400x100	3,4	200	20	Pneumatic	4ply rubber	Steel, gray powdercoated	M-800-L4-20	11177
250	400-8/16x4" 400x100	3,4	250	20	Pneumatic	4ply rubber	Steel gray powdercoated	M-800-L4-25	11443