for safe storage

PRODUCT DATA SHEET


CEMO Rectangular container with forklift pockets, 700 L, grey

Order no.: 2554

PRODUCT DESCRIPTION

- reinforced gripping rim for excellent inherent rigidity
- smooth surfaces inside and outside for easy cleaning
- corrosion-resistant and extremely light
- high strength with a high degree of stability
- UV-resistant for use outdoors
- less dirt thanks to smooth external walls
- no residues left behind after draining due to smooth internal walls in the container
- high-precision fit of the optional lid thanks to reinforced gripping rim
- mounted forklift pockets are impervious to liquids
- specifically designed for rotary forklifts





TECHNICAL DATA

Content volume	700 l
External dimensions (lxh)	132 x 97 x 88 cm
Internal dimensions (lxh)	118 x 83 x 80 cm
Weight	40 kg
Material	GRP
Coating	uncoated
Container colour	grey
Stackable	yes
Warranty in years	10

LOGISTICS

Package dimensions (l x w x h)	145 x 100 x 145 cm
Units per box	1
Units per pallet	10

for safe storage

Pallet dimensions	140 x 100 x 145 cm
Shipping weight	50 kg
Freight	General cargo
Customs tariff number	39251000

ACCESSORIES



1172 - Lid for rec. container 550L, 700L, grey



1303 - Discharge valve ¾" with inside thread



1304 - Discharge valve 1" with 1" internal thread



1305 - Discharge valve 1 ¼" with internal thread



1306 - Discharge valve 1 ½" with 1 ½" internal thread



1307 - Discharge valve 2" with inside thread



1314 - Spindle valves (plastic) ½"



1315 - Spindle valves (plastic) ¾"



1393 - Brass screw-through thread R3/4"



1394 - Screw through threaded connector 1"



1395 - Screw through threaded connector 1 ¼"



1396 - Screw through threaded connector 1 ½"



1397 - Screw in threaded connector ¾" nickel-plated



1398 - Screw in threaded connector 1" nickel-plated



1399 - Screw in threaded connector 1 ¼" nickel-plated



1500 - Screw in threaded connector 1 ½" nickel-plated



1501 - Screw in threaded connector 2" nickel-plated



1515 - Screw in threaded connector ET 1" IT ½" plastic



1516 - Screw in threaded connector ET 1 ¼" IT ¾" plastic




1517 - Screw in threaded connector ET 1 ¼" IT 1" plastic




1518 - Screw in threaded connector ET 2" IT 1 ½" plastic




1519 - Screw in threaded connector ET 2 ¾" IT 2" plastic




1752 - Pipe coupling (PVC) 3/4"




1753 - Pipe coupling (PVC) 1"



1754 - Pipe coupling (PVC) 1 1/4"



1755 - Pipe coupling (PVC) 1 1/2"



1756 - Pipe coupling (PVC) 2"



6426 - Plastic ball valve (PVC) 1" with inside thread



6428 - Plastic ball valve (PVC) 1 ½" with inside thread



6429 - Plastic ball valve (PVC) 2" with inside thread



6430 - Plastic ball valve (PVC) 3"

for safe storage

Link to product

Technical specifications subject to change/Errors and omissions excepted. © CEMO 2554-en 11.26
CEMO GmbH | In den Backenländern 5 | 71384 Weinstadt | Germany | Tel. +4971519636-0 | kontakt@cemo-group.com