for safe storage

PRODUCT DATA SHEET

Fuel extraction units, 95 L, Automatic dispensing nozzle petrol, 12 V DC, 25 L/min (max.), black, castors

Order no.: 10762

PRODUCT DESCRIPTION

- electrically operated extraction and refuelling unit for fuels, 2-stroke mixture and diesel
- ideal in case of misfuelling, accidents or vehicle return
- Integral flashback arrestor in the container for improved safety
- 2 m extraction hose (DN 10) and 3.2 m dispensing hose (DN 19)
- 12 VDC pump with 3 m connection cable with crocodile clips and earthing cable with crocodile clips
- automatic dispensing nozzle and dispensing hose for unleaded petrol
- switch between extraction and refuelling via ball valves
- two flexible sensors (ø 8 mm/1,500 mm and ø 12 mm/ 700 mm)
- adapters for hoses ø 6 mm and ø 10 mm
- holder for sensors and adapters (not mounted on the trolley)





TECHNICAL DATA

Content volume	95 l
External dimensions (lxh)	56 x 45 x 100 cm
Weight	23 kg
Material	LLDPE
Place of installation	Indoor
Container colour	black
Stackable	No
Coating	uncoated
Operating voltage	12 V DC
Pump drive	Pump
Max. flow rate	25 L/min (max.)
Warranty in years	1

EQUIPMENT

Feet/castors	With castors
Hose reel	No
Over-fill sensor	No
Bund leak indicator	No
Heating	No

SUITABLE STORAGE MEDIA

Petrol

LOGISTICS

Package dimensions (l x w x h)	80 x 60 x 120 cm
Units per box	1
Units per pallet	4
Pallet dimensions	140 x 100 x 215 cm
Shipping weight	40 kg
Freight	General cargo
Customs tariff number	84131100

ACCESSORIES



10411 - Digital flow meter K24 (petrol) alu, ATEX/IECEx, for KS-Mobile Easy

Link to product

Technical specifications subject to change/Errors and omissions excepted. © CEMO 10762-en 11.26
CEMO GmbH | In den Backenländern 5 | 71384 Weinstadt | Germany | Tel. +4971519636-0 | kontakt@cemo-group.com